

Agile™



SECUREIT™

Ammo Cabinet – Upper 14 Part Number: AG-AC14-UPPER



Product Specifications:

- W x D x H (External) 20-1/4" x 15-1/4" x 14"
- W x D x H (Internal) 20" x 14-1/8" x 13-13/16"
- Weight: 43 pounds
- 14 Gauge Steel Cabinet and Door, 16 Gauge Steel Louvered Back Panel
- **Maximum top load capacity: 300 pounds**

The Agile™ Ammo Cabinet arrives locked, with the two override keys attached to the outside of the door.

Fully insert the key and turn clockwise to unlock. Turn the key counter-clockwise to lock.

Please Note: Do not throw away the packaging until you've located the keys.

Do you have questions or need help? Contact us by e-mail or phone.

E-mail: Support@SecureItTactical.com

Phone: 1-800-651-8835

Hours of Operation: 8:00 AM to 4:30 PM Eastern, Monday to Friday

SecureIt Limited Lifetime Warranty

SecureIt products shall be free from defects in material and workmanship for life. This warranty applies only to new products purchased from SecureIt or its authorized distributors and dealers. Must provide proof of purchase to obtain service under this warranty. This warranty does not apply to damage or loss resulting from accident, misuse, improper installation, scratching of paint, normal wear and tear, or negligence. The responsibility of SecureIt under this warranty is limited to replacement or repairs of defective parts with all transportation charges paid by the original purchaser.

Follow Us On:

Facebook - [Facebook.com/GunStorage](https://www.facebook.com/GunStorage)

Twitter - [@SecureItStorage](https://twitter.com/SecureItStorage)

Instagram - [@SecureIt](https://www.instagram.com/SecureIt)

YouTube - [YouTube.com/SecureItGunStorage](https://www.youtube.com/SecureItGunStorage)



The Agile™ Ammo Cabinet is designed to mount on top of an Agile™ Model 40 safe, Agile™ Model 52 safe, or it can be used as a stand alone ammo cabinet.

The top load weight capacity should not exceed 300 pounds.

Mounting your Ammo Cabinet to an Agile™ Safe

Parts List:

H-1. Screws (4 ct.)

H-2. Fender Washers (8 ct.)

H-3. Nylon Lock Nuts (4 ct.)

Tools Needed:

10mm Wrench

Phillips-Head Screwdriver



H-1.



H-2.



H-3.

CAUTION: Serious injuries can occur from safe tip-over.

Step 1 – Anchor the Agile™ safe to the floor or wall before mounting the Ammo Cabinet on top.

Step 2 – Safely lift and place the Ammo Cabinet on top of the Agile™ safe.

Step 3 – Insert a screw (H-1) through a fender washer (H-2), then push the screw through the hole on the bottom of the Ammo Cabinet into the hole on the top of the Agile™ safe. Repeat this step for the three remaining mounting holes.

Step 4 – Inside the Agile™ safe, slide a fender washer (H-2) over the screw (H-1), then hand tighten a nylon lock nut (H-3) onto the screw. Repeat this step for the three remaining screws.

Step 5 – Use a screwdriver and wrench to tighten all the screw and nylon lock nut connections.

Step 3:



Step 4:

